

SC Single Mode Fiber Optic Connector

Quick Details

Place of Origin: Shenzhen, China (Mainland);
Brand Name: OPTICO;
Model Number: Fiber Optic Adapter, SC/APC Connector and Adapter;
Type: APC/PC/UPC;
Color: Blue,Green,Grey;
Insertion Loss: IL<0.2db;
Mode: Singlemode;
Quality: high quality fiber optic adapter;
Durability: >1000 matings;
Sleeve: Zirconia;
Operating Temperature: -40~75°C;
Return Loss: > 50db;

Packaging Details:

SC/APC SM SX Fiber Optic Adapter/SC Adaptor Fiber Optic Connector in 25pcs/pack; 4 cartons(26cm*26cm*26cm) in a bigger cartons(40cm*50cm*50cm);

Delivery Time:

within 3~7 days for SC/APC Connector and Adapter;



SC/APC SM SX Fiber Optic Adapter/SC Adaptor Fiber Optic Connector

Product Description:

Fiber optic adapters are used to provide a cable to cable or cable to equipment fiber optic connection. We supply a wide range of mating sleeves and hybrid adapters, including special male to female hybrid fiber optic adaptor.

Feature:

1. Low insertional loss and high return loss;
2. High precision alignment;
3. Nickel plated brass body;
4. Use in Single-mode or Multimode applications;

- 5 .Choice of housing material and sleeve material;
- 6. ISO9001:2008,ROHS compliance;

Applications:

- 1.Fiber Optic Telecommunications;
- 2.LAN (Local Area Network);
- 3.FTTTH (Fiber To The Home);
- 4.CATV&CCTV System;
- 5.High speed transmission systems;
- 6.Fiber optic sensing;
- 7.Industrial, Mechanical and Military;

Specification:

Parameter	Unit	LC, SC, FC, ST				
					SM	MM
		PC	UPC	APC	PC	
Insertion Loss (Typical)	dB	≤0.2	≤0.2	≤0.2	≤0.2	
Return Loss	dB	≥50	≥50	≥60	≥40	
Exchangeability	dB	≤0.2				
Repeatability	dB	≤0.2				
Durability	Time	>1000				
Operating Temperature	°C	-40~75				
Storage Temperature	°C	-45~85				

Shipping Ways:



Company Pictures:

